

PRODUCT SPECIFICATIONS

Performance	
Nominal Volumetric Air Flow Rate (CFM)	2,000
External Static Pressure (in. of W.C.)	1.1
UVC Light Power Rating (W)	3 x 100
UVC Light Kill Capacity (%)	99.99
HEPA Filtration Capacity (%)	99.97
Noise Level (dbA @ 3m)	72
Electrical	
Voltage (VAC)	115 ±10%
Phase	1
Frequency (Hz)	60
Rated Current (Amps)	13.8
Rated Power (kW)	1.6
Circuit Breaker Size (A)	10
Physical Characteristics	
Unit Dimensions (H x W x D) (in)	53.3 x 24.4 x 48.3
HEPA Filter Dimensions (H x W x D) (in)	24 x 24 x 12
Carbon Filter Dimensions (H x W x D) (in)	24 x 24 x 2
Supply & Return Duct Take-offs Dia. (If Equipped) (in)	16
Unit Weight (Lbs)	262



Indoor Grilles Configuration



Ducted Configuration

KEY FEATURES

- Steril-Aire UVC (kills up to 99.9999% of airborne pathogens)
- HEPA Filter (captures 99.97% of 0.3-micron particles)
- Carbon Filter (removes gases and other VOC's)
- 1" Washable Pre-Filter
- Air Turbulator
- High-Static EC Blower (up to 2" w.c.)
- Variable Speed Control
- 16" Duct Take-offs (Inlet and Outlet)
- Optional Indoor Air Grilles
- Twin 6" Pressure Relief Ports (for negative pressure)
- Run Time Hour Meter
- Lightweight Aluminum Construction
- Forklift Pockets
- Flat Free Swivel Casters (Indoor configuration)
- Pull Handles
- Powder Coated Finish
- Limited 1 Year Warranty