

Operating Power: 208-230VAC±10%, 3-Phase, 60Hz
 Nominal Cooling Capacity: 10 Tons
 Nominal Heating Capacity: N/A

PRODUCT SPECIFICATIONS	
PERFORMANCE	
Cooling BTU/Hr @ 80°F DB, 67°F WB, 95°F Ambient	120,000
Heating BTU/Hr	N/A
Operating Conditions (°F)	55 to 105
Operating Conditions with Low Ambient Control (°F)	N/A
Evaporator Supply Air Flow Rate (CFM)	4000
Compressor Operating Mode	ON/OFF
ELECTRICAL	
Voltage (VAC) ±10%	208-230
Phase	3
Frequency (Hz)	60
Maximum Current - Cooling (A)	46.4
Maximum Current - Heating (A)	N/A
Maximum Power Consumption - Cooling (kW)	14.8
Electric Heat (kW)	N/A
Circuit Breaker/Fuses Size (A)	60
Supply Power Cord Size (AWG)	6
PHYSICAL CHARACTERISTICS	
Dimensions, H x W x D (in)	85.125 x 48 x 27.375
Weight, Unit (Lbs)	1015
Fan Type, Evaporator	Belt Drive, Forward-Inclined Centrifugal
Fan Type, Condenser	n/a
Evaporator Supply Air Duct Nozzles Qty.	10
Evaporator Supply Air Duct Nozzles Nominal Dia. (in)	5
Caster Height (in)	5
REFRIGERANT	
Type	R-410a
Charge (oz)	See unit data plate.



PRODUCT KEY FEATURES

- Heavy-Duty 18-gauge Steel Cabinet
- High-Efficiency, Tube-and-Fin Evaporator Coil
- High-Efficiency Coaxial Condenser Coil
- High-Efficiency Forward-Inclined Centrifugal Evaporator Fan
- Best-in-Class Scroll Compressor with Thermal Overload Protection
- Environment-Friendly Refrigerant R-410a
- Electronic Thermostat
- Power Cord with flying leads
- Hot Gas Bypass for Frost Control
- Externally Accessible Refrigerant Sight Glass and Servicing Ports
- Permanent Washable Air Filters
- Adjustable Directional Air Nozzles (Adjust 180°)
- Stainless Steel Condensate Drain Pan with Float Switch; Shuts Down System, if Clogged;
- Condensate Pump
- Durable Plastic Grab Handles for Additional Maneuverability
- Heavy-Duty Caster (All Swivel, Two with Brakes)
- Durable Powder Coat Finish

All specifications are subject to change without notice.