

PRODUCT SPECIFICATIONS

Performance

NA 2,000 3,500 69
2,000
NA
55 to 105
NA
72,000
62,500

Voltage (VAC) ±10%	208/230
Phase	1
Frequency (Hz)	60
Maximum Nominal Current - Cooling (A)	47.5
Maximum Nominal Current - Heating (A)	NA
Maximum Nominal Power Consumption - Cooling (kW)	8.7
Electric Heat (kW) @ 230VAC(*)	NA
NEMA Plug Configuration	NA (pigtail)
Circuit Breaker/Fuses Size (A)	80
Supply Power Cord Size (AWG)	6

Physical Characteristics

Dimensions, H x W x D (in)	72.25 x 46 x 32
Unit Weight/Shipping Weight (Lbs)	624/729
Fan Type, Evaporator	Belt Drive
Fan Type, Condenser	Belt Drive
Caster Height (in)	5
Directional Supply Air Nozzles Qty/Diameter (in)	6/5

Refrigerant

Туре	R-410a
Charge (oz)	152

(*) Heating elements are factory-rated 15kW at 240VAC and de-rated to 13.8kW when operating at 230VAC. All specifications are subject to change without notice



KEY FEATURES

- » Heavy duty 18 ga precision sheet metal cabinet
- » Adjustable directional air nozzles. Adjust 180° and tuck away for safe and easy transport
- » Programmable Thermostat (24Vac), unit- or wall-mounted Can interface with building computer operation systems
- » Externally accessible servicing ports and sight glass
- » Hinged condenser filter access door
- » 5 gallon condensate recovery
- » Heavy duty industrial casters (all swivel, 2 with brakes)
- » Powder coat finish (durable, scratch-resistant)
- » Independent evaporator and condenser motors (high static, high volume)
- » Removable, permanent washable condenser and evaporator filters
- » Vacuum-formed internal drain pan with two drain openings on opposite corners. Unit shuts off if clogged.
- » High quality coils (enhanced lanced aluminum finish, rifled copper tubing)
- » High efficiency compressor
- » Built-in condenser air intake and exhaust plenums